



**PRODUCT CODE:** RE-DISDU-FFP1

**PRODUCT DESCRIPTION:** AIRMAXX DISPOSABLE FFP1 DUST MASK

## MATERIALS

<b>NOSECLIP</b>	Aluminium strip, glue bonded.
<b>MASK/RESPIRATOR</b>	3 layers – top and bottom are non-woven 100% polyester, middle layer is meltblown nonwoven polyester.
<b>HEAD STRAPS</b>	Spandex elastic tape, glue bonded to mask.

## COMPLIANCY

EN 149



## CERTIFICATION

<b>EN/ISO REQUIREMENT</b>	EN 149:2001
<b>PROTECTION RATING</b>	FFP1 NR
<b>CE REQUIREMENT</b>	CE 0194
<b>SABS</b>	SANS 50149:2003
<b>NRCS</b>	NRCS/8072/0162

## SPECIAL FEATURES

- Low profile dust mask with adjustable noseclip to ensure a better fit (especially with glasses and goggles) and minimum ingress of dust particles.
- Protects against materials in concentrations up to 4x OEL (Occupational Exposure Limit) or 4x APF (Assigned Protection Factor).
- Pre-stretched, latex-free head straps.
- Protects against low levels of dust, as well as solid and liquid aerosols.

## WARNINGS

- This product will not protect against fumes, gases or vapours.
- This product does not supply oxygen. Ensure that you use it in well ventilated areas containing sufficient oxygen.
- This is a single use respirator. Discard it after a single shift, or after 8 hours of use.
- Leave work area immediately if breathing becomes difficult, or dizziness occurs.
- Consult your Safety Officer or an approved sales rep when implementing a respiratory protection programme.

## OTHER INFORMATION

<b>SIZING</b>	20 individual masks in a ziplock sealed packet.
<b>PACKAGING</b>	50 packs per carton (1000 masks).
<b>STORAGE</b>	Respirators must be placed in a sealed packet or container, and stored in an environment free of dust, chemicals, moisture, excessive heat and direct sunlight. Failure to do so may affect the performance and shelf life of these products.

## SUGGESTED ENVIRONMENTS

FFP1 Dust Masks are ideal for low level dust environments i.e. hand sanding, drilling and cutting.