



**PRODUCT CODE:** HS-CLHHEL

**PRODUCT DESCRIPTION:** Climbing helmet with adjustable chin strap

## PRODUCT COMPLIANCE

CERTIFICATION	EN12492:2012
WEIGHT	490gms
COLOUR AVAILABILITY	White
PACKAGING	Individually packed in a box, 12 units per carton
SIZING	Adjustable to fit head with circumference of 56cm to 63 cm

## MATERIALS + DESIGN

- Outer Shell made with Acrylonitrile Butadiene Styrene (ABS).
- High protective shell exterior.
- Ventilation holes with sliding shutters.
- Inside protection in high-density polystyrene (EPS) which aids with impact resistance protection.
- Inner textile and headband, removable and washable.
- Polyester webbing chin strap which includes a synthetic leather strap.

## TECHNICAL FEATURES

- Protection from falling objects.
- Protection from side impact.
- Wheel ratchet provides quick and easy size adjustment.
- Adjustable chin strap (4-point chin strap), which includes a synthetic leather strap for added comfort.
- Interior EPS for comfort and added protection.
- Head lamp slots for attaching a head lamp that works with an elastic strap.
- Spectacle visor attachment (visor not included).
- Fully certified for mountaineering/work at height environments.

## USER ADVICE

- This helmet is made to absorb the energy from falling objects and side impact, and even though such damage may not be readily apparent, any product subjected to severe impact should be replaced.
- Do not modify or remove any of the original component parts of the product.
- This product comes with standard fittings for a headlamp, visor and earmuffs (supplied separately).
- This product should not be adapted for the purpose of fitting any extra attachments.
- Do not apply paints, solvents, adhesives or self-adhesive labels. The product may be adversely affected by certain chemicals.
- Clean any part of the safety helmet with warm soapy water and dry with a soft cloth.

## ADJUSTMENT AND FITTING

- To ensure adequate protection is provided by the product, the wheel ratchet at the back of the helmet must be adjusted according to the size of the user's head, This must be done until the helmet feels comfortable and snug on the user's head. Do not over tighten.

## STORAGE

- When not in use, it is recommended to store the industrial helmet in a clean and dry polybag or case for optimal protection.
- Storage temperature range: -10°C to +50°C.

## DURATION OF USE

- To be inspected for damage regularly by a competent person.
- If the shell shows any signs of damage, it must be replaced immediately.
- Replace after no more than two years of regular use or five years from the date of manufacture, which is a clock dial imprinted on the inside of the helmet.

## WARNINGS

- Be sure to always wear your helmet with the chin strap **securely** clipped in, to make sure it does not fall off in case of any slip or fall incident.
- Working at heights training must be completed prior to using this product, if used when working at heights.
- This helmet has no electrical insulation rating. **DO NOT USE THIS HELMET IN AN ELECTRICAL HAZARDOUS ENVIRONMENT.**

## SUGGESTED ENVIRONMENTS

- Working at Heights.
- Confined Spaces.
- General work.